


WAAS CH 87129 W19A	APP CRS 189°	Rwy Idg TDZE 898 Apt Elev 898
--	------------------------	---

RNAV (GPS) RWY 19

WARREN COUNTY/JOHN LANE FLD (I68)

RNP APCH.	Rwy 19 helicopter visibility reduction below 1 SM NA. When local altimeter setting not received, use Dayton/Wright Brothers altimeter setting and increase all MDAs 40 feet, and LP and LNAV Cat C and D visibilities ½ SM and Circling Cat C visibility ¼ SM. Straight-in Rwy 19 and Circling Rwy 19 at night, operational VGSI required, remain on or above VGSI glidepath until threshold.	MISSED APPROACH: Climb to 3000 direct WUSPU and hold.
-----------	---	--

AWOS-3PT 120.55	COLUMBUS APP CON 118.85 269.275	CLNC DEL 119.4	UNICOM 123.075 (CTAF) 0
---------------------------	---	--------------------------	-----------------------------------



MIRL Rwy 1-19 **1**
REIL Rws 1 and 19 **1**

3000		WUSPU		VGSI and RNAV glidepath not coincident (VGSI Angle 3.50/TCH 35).		
1.4 NM		2.8 NM		5.7 NM		
CATEGORY	A		B		C	D
LP MDA	1280-1		382 (400-1)		1280-1½	382 (400-1½)
LNAV MDA	1320-1		422 (500-1)		1320-1¼	422 (500-1¼)
C CIRCLING	1400-1 502 (600-1)		1480-1 582 (600-1)		1480-1½ 582 (600-1½)	1480-2 582 (600-2)