

WAAS
CH **86299**
W25A

APP CRS
256°

Rwy Idg
TDZE **44**
Apt Elev **45**

RNAV (GPS) RWY 25

OXNARD (OXR)

⚠

RNP APCH-GPS.

⚠

Inoperative table does not apply. Baro-VNAV NA when using Camarillo altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 43°C. When local altimeter setting not received, use Camarillo altimeter setting and increase LPV DA to 312 feet, increase LNAV/VNAV DA to 351 feet; increase all MDAs 20 feet and Circling Cat C visibility ¼ SM.

MALSF

⚠

MISSED APPROACH: Climb to 2000 direct PEWKI and on track 239° to SQUID and hold.

ATIS 118.05	POINT MUGU APP CON* 124.7 335.5	OXNARD TOWER* 134.95 (CTAF) 0 257.8	GND CON 121.9
-----------------------	---	---	-------------------------

ELEV 45	D	TDZE 44		
REIL Rwy 7 MIRL Rwy 7-25 2000 PEWKI tr 239° SQUID CUDAK HUPLA NELLY CUKUM 5.1 NM to RW25 RW25 5.1 NM 4.6 NM 3 NM 3.4 NM GP 3.00° TCH 58				
CATEGORY	A	B	C	D
LPV DA	294-1 250 (300-1)			
LNAV/VNAV DA	333-1 289 (300-1)			
LNAV MDA	520-1 476 (500-1)		520-1 ³ / ₈ 476 (500-1 ³ / ₈)	
CIRCLING	520-1 475 (500-1)		700-1 ³ / ₄ 760-2 ¹ / ₄ 655 (700-1 ³ / ₄) 715 (800-2 ¹ / ₄)	

OXNARD, CALIFORNIA

Amtd 1C 04NOV21

34°12'N-119°12'W

OXNARD (OXR)

RNAV (GPS) RWY 25